

Opony szutrowe R700, R800, R900

ROZMIAR OPONY	MIESZANKI	Średnica opony	Szerokość opony	Szerokość bieżnika	Optymalna szerokość felgi	Tolerancja felgi	OBR/ MILA
		(MM)	(MM)	(MM)	(INS)	(INS)	
165/80R13 R700	K90,K70	631	173	135	5	4.5-6.0	812
175/70R13 R800	K90,K70,K30	582	176	148	5	4.5-6.0	880
185/70R13 R800	K90,K70,K30	595	191	161	5,5	5.0-6.0	860
195/70R13 R700	K90,K70	608	203	161	6	5.5-6.5	843
195/70R13 R800	K90,K70,K30	608	200	168	6	5.5-6.5	840
175/65R14 R700	K90,K70	590	174	140	5	5.0-6.0	869
175/65R14 R800	K90,K70,K30	590	178	148	5	5.0-6.0	868
185/65R14 R700	K90,K70	602	186	147	5,5	5.0-6.5	851
175/70R15 R800	K90,K70,K30	632	180	150	5	5.0 - 6.0	810
185/60R15 R700	K90,K70	610	189	156	5,5	5.0-6.5	840
185/60R15 R800	K90,K70,K30	610	190	162	6	5.0-6.5	840
195/65R15 R700	K90,K70	641	191	157	6	5.5-7.0	799
195/65R15 R800	K90,K70,K30	640	204	164	6	5.5-7.0	800
205/60R15 R700	K90,K70	641	209	180	6	5.5-7.5	799
205/65R15 R800	K90,K70,K30	647	209	181	6,5	6.0-7.0	792

ECSTA V70A

ROZMIAR OPONY	MIESZANKI	Średnica opony	Szerokość opony	Szerokość bieżnika	Optymalna szerokość felgi	Tolerancja felgi	OBR/ MILA
		(MM)	(MM)	(MM)	(INS)	(INS)	
175/60HR13	K90,K60,K20	537	178	170	6	5.5-6.5	954
215/50VR13	K90,K60,K20	540	226	203	8	7.0-8.0	949
235/45VR13	K90,K60,K20	536	236	216	9	7.5-9.0	956
185/55VR14	K90,K60,K20	554	190	172	6	5.0-6.5	925
195/55VR14	K90,K60	565	196	175	6	5.5-7.0	907
225/50WR14	K90,K60	575	227	205	7	6.0 - 8.0	891
185/55VR15	K90,K60,K20	581	187	169	6	5.0-6.5	882
195/55WR15	K90,K60,K20	590	195	190	6	5.5 - 7.0	868
205/50ZR15	K90,K60,K20	583	207	186	6,5	6.0-8.0	877
225/45WR15	K90,K60	578	225	208	7,5	7.0-8.5	886
225/50ZR15	K90,K60,K20	600	228	206	7	7.0-8.5	854
205/45VR16	K90,K60,K20	585	201	188	7	6.5-7.5	876
225/50WR16	K90,K60,K20	626	228	210	7	6.0-8.0	818
205/40WR17	K90,K60	595	203	187	7,5	7.0-8.0	861
215/45WR17	K90,K60	622	219	217	7,5	7.0-8.0	824
225/45WR17	K90,K60	628	224	207	7,5	7.0-8.5	816
235/40WR17	K90,K60	614	240	222	8,5	8.0-9.5	834
275/40WR17	K90,K60	647	270	254	9,5	9.0-11.0	792
225/40WR18	K90,K60	631	229	212	8	7.5-9.0	812
245/35WR18	K90,K60,	624	251	234	8,5	8.0-9.5	821
265/35WR18	K90,K60	637	263	249	9,5	9.0-10.5	804
285/30WR18	K90,K60	623	274	266	10	9.5-11.0	822

Rajdy asfaltowe – C03, TW01, TW02

ROZMIAR OPONY	MIESZANKI	Średnica	Szerokość	Szerokość	Optymalna	Tolerancja	OBR/
		opony	opony	bieżnika	szerokość felgi	felgi	MILA
		(MM)	(MM)	(MM)	(INS)	(INS)	
180/530R13 C03	K60,K20,K10	530	188	184	6,5	6.0 - 7.0	967
200/530R13 C03	K90,K60,K20,K10	530	224	198	7,5	6.0 - 8.0	967
160/570R14 C03	K90,K60,K20,K10	570	185	157	6,5	5.5 - 7.0	898
180/580R15 C03	K90,K60,K20,K10	580	191	171	6,5	6.0 - 7.5	883
180/580R15 TW01	K20,K10	580	184	175	6,5	6.0 - 7.5	883
200/580R15 C03	K90,K60,K20,K10	580	223	196	8	7.5 - 9.0	883
160/630R16 TW01	K20,K10	628	201	163	7	6.0 - 7.5	816
170/630R16 C03	K90,K60,K20,K10	628	201	166	7	6.0-7.5	816
200/615R16 C03	K90,K60,K20,K10	616	219	194	7,5	6.5-8.0	832
160/630R17 TW01	K20,K10	628	190	165	7	6.0-7.5	816
170/630R17 C03	K90,K60,K20,K10	628	187	174	7	6.0-7.5	816
200/615R17 C03	K90,K60,K20,K10	616	211	200	7,5	7.0-8.0	832
200/640R17 TW01	K20,K10	642	221	189	8	7.0 - 8.5	798
220/640R17 C03	K90,K60,K20,K10	643	221	207	8	7.5-9.0	797
200/640R18 TW01	K20,K10	640	222	195	8	7.0-8.5	800
220/645R18 C03	K90,K60,K20,K10	639	227	208	8	7.5-9.0	802